

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: August

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

| Alleima | GRADE | | ALLOY & ENERGY SURCHARGE PER KG | | | | | | | | | | | |
|--|------------|--------|---------------------------------|--------|-------|-------|-------|-------|-------|--------|-------|---------|---------|-------|
| | W.nr | ASTM | SS | SEK | EUR | GBP | USD | JPY | CAD | CNY | CHF | Lbs USD | Lbs CAD | BRL |
| Alloyed non-stainless steels and carbon steels | | | | | | | | | | | | | | |
| 20C | 1.1274 | 1095 | 1870 | 5,40 | 0,48 | 0,40 | 0,51 | 82 | 0,70 | 3,73 | 0,46 | 0,23 | 0,32 | 2,81 |
| 20C2 | | | 2258 | 5,90 | 0,52 | 0,44 | 0,56 | 90 | 0,77 | 4,07 | 0,50 | 0,25 | 0,35 | 3,07 |
| 10C16Mo3V1 | | | | 19,02 | 1,68 | 1,42 | 1,81 | 289 | 2,47 | 13,13 | 1,62 | 0,82 | 1,12 | 9,89 |
| Sanprint XP | | | | 18,13 | 1,60 | 1,35 | 1,72 | 276 | 2,36 | 12,51 | 1,54 | 0,78 | 1,07 | 9,43 |
| **** | | | | | | | | | | | | | | |
| Martensitic stainless chromium steels | | | | | | | | | | | | | | |
| 6C27 | 1.4007 | 420 | 2234 | 10,91 | 0,96 | 0,81 | 1,04 | 166 | 1,42 | 7,53 | 0,93 | 0,47 | 0,64 | 5,67 |
| 7C27Mo2 | | | | 18,29 | 1,61 | 1,36 | 1,74 | 278 | 2,38 | 12,62 | 1,56 | 0,79 | 1,08 | 9,51 |
| Hiflex | | | | 18,29 | 1,61 | 1,36 | 1,74 | 278 | 2,38 | 12,62 | 1,56 | 0,79 | 1,08 | 9,51 |
| Freeflex | | | | 19,27 | 1,70 | 1,44 | 1,83 | 293 | 2,50 | 13,30 | 1,64 | 0,83 | 1,14 | 10,02 |
| 10C28MO2 | | | | 18,50 | 1,63 | 1,38 | 1,76 | 281 | 2,40 | 12,77 | 1,57 | 0,80 | 1,09 | 9,62 |
| 12C27M | | | | 11,23 | 0,99 | 0,84 | 1,07 | 171 | 1,46 | 7,75 | 0,96 | 0,48 | 0,66 | 5,84 |
| 12C27 | | | | 10,84 | 0,96 | 0,81 | 1,03 | 165 | 1,41 | 7,48 | 0,92 | 0,47 | 0,64 | 5,64 |
| 14C28N | | | | 11,03 | 0,97 | 0,82 | 1,05 | 168 | 1,43 | 7,61 | 0,94 | 0,48 | 0,65 | 5,74 |
| 13C26 | | | 14141 | 10,60 | 0,94 | 0,79 | 1,01 | 161 | 1,38 | 7,32 | 0,90 | 0,46 | 0,62 | 5,51 |
| Damax | | | | 14,57 | 1,29 | 1,09 | 1,38 | 221 | 1,89 | 10,05 | 1,24 | 0,63 | 0,86 | 7,58 |
| 19C27 | | | | 10,84 | 0,96 | 0,81 | 1,03 | 165 | 1,41 | 7,48 | 0,92 | 0,47 | 0,64 | 5,64 |
| **** | | | | | | | | | | | | | | |
| Austenitic stainless steels | | | | | | | | | | | | | | |
| 12R11 | 1.4310 | 301 | 2331 | 26,43 | 2,33 | 1,97 | 2,51 | 402 | 3,43 | 18,24 | 2,25 | 1,14 | 1,56 | 13,75 |
| 11R51 | 1.4310 | 301 | 2231 | 31,36 | 2,77 | 2,34 | 2,98 | 476 | 4,07 | 21,64 | 2,67 | 1,35 | 1,85 | 16,31 |
| 13RM19 | EN 1.4369 | | | 26,85 | 2,37 | 2,00 | 2,55 | 408 | 3,49 | 18,53 | 2,28 | 1,16 | 1,58 | 13,97 |
| 3X22R60HV | 1,4441 | 316LVM | | 60,82 | 5,37 | 4,54 | 5,78 | 924 | 7,90 | 41,98 | 5,17 | 2,62 | 3,58 | 31,64 |
| 2RK65HV | | | | 90,49 | 7,99 | 6,75 | 8,59 | 1 375 | 11,75 | 62,45 | 7,70 | 3,90 | 5,33 | 47,07 |
| 3X8R65 | | | | 47,58 | 4,20 | 3,55 | 4,52 | 723 | 6,18 | 32,84 | 4,05 | 2,05 | 2,80 | 24,75 |
| 3R60F1 | | | | 58,85 | 5,19 | 4,39 | 5,59 | 894 | 7,64 | 40,62 | 5,01 | 2,54 | 3,47 | 30,61 |
| **** | | | | | | | | | | | | | | |
| Precipitation hardenable steels | | | | | | | | | | | | | | |
| 9RU10 | 1.4568 | 631 | 2388 | 26,75 | 2,36 | 2,00 | 2,54 | 406 | 3,47 | 18,46 | 2,28 | 1,15 | 1,58 | 13,91 |
| NANOFLEX | | | | 59,77 | 5,27 | 4,46 | 5,68 | 908 | 7,76 | 41,25 | 5,09 | 2,58 | 3,52 | 31,09 |
| 1RK95 | | | | 26,31 | 2,32 | 1,96 | 2,50 | 400 | 3,42 | 18,16 | 2,24 | 1,13 | 1,55 | 13,69 |
| **** | | | | | | | | | | | | | | |
| Duplex stainless steels (austenitic-ferritic) | | | | | | | | | | | | | | |
| SAF2205 | EN 1.4462 | | 2377 | 48,90 | 4,32 | 3,65 | 4,64 | 743 | 6,35 | 33,75 | 4,16 | 2,11 | 2,88 | 25,43 |
| SAF2507 | EN 1.4410 | | 2328 | 57,22 | 5,05 | 4,27 | 5,44 | 870 | 7,43 | 39,49 | 4,87 | 2,47 | 3,37 | 29,77 |
| SAF3207HD | | | | 56,75 | 5,01 | 4,23 | 5,39 | 862 | 7,37 | 39,17 | 4,83 | 2,45 | 3,34 | 29,52 |
| **** | | | | | | | | | | | | | | |
| Ferritic stainless chromium steel | | | | | | | | | | | | | | |
| 1C429 | | | | 14,93 | 1,32 | 1,11 | 1,42 | 227 | 1,94 | 10,31 | 1,27 | 0,64 | 0,88 | 7,77 |
| 1C44Mo20 | | | | 21,77 | 1,92 | 1,62 | 2,07 | 331 | 2,83 | 15,02 | 1,85 | 0,94 | 1,28 | 11,32 |
| 0XC34 | | | | 12,28 | 1,08 | 0,92 | 1,17 | 187 | 1,59 | 8,47 | 1,04 | 0,53 | 0,72 | 6,39 |
| 1C34 | | | | 12,19 | 1,08 | 0,91 | 1,16 | 185 | 1,58 | 8,42 | 1,04 | 0,53 | 0,72 | 6,34 |
| **** | | | | | | | | | | | | | | |
| Nickel-base alloy | | | | | | | | | | | | | | |
| SANICRO75X2 | UNS N07750 | | | 151,46 | 13,37 | 11,30 | 14,39 | 2 301 | 19,67 | 104,53 | 12,89 | 6,53 | 8,92 | 78,78 |
| SAN62TiNb | | | | 132,07 | 11,65 | 9,85 | 12,54 | 2 007 | 17,15 | 91,15 | 11,24 | 5,69 | 7,78 | 68,70 |
| **** | | | | | | | | | | | | | | |
| Energy surcharge per kg included in total surcharge | | | | 1,08 | 0,10 | 0,08 | 0,10 | 16 | 0,14 | 0,74 | 0,09 | 0,05 | 0,06 | 0,56 |